

# A.S.I.

AUSTRALASIAN SHINGLE IMPORTERS  
SUPPLY & FIXERS OF IMPORTED ASPHALT SHINGLES

P O BOX 81 MORNINGTON 3931  
A C N 087 873 327

22 CARBINE WAY MORNINGTON 3931  
TEL: 03 5975 4944 MOB: 0412 070 146  
FAX: 03 5975 2752

## **CERTAINTEED SPECIFICATION INFORMATION** **XT25 Roofing Shingles**

### ***Product Description***

XT25 Roofing Shingles are designed for use on sloped roofs only. An extra heavy, 3-tab construction combines exceptional durability with flexibility.

XT25 Shingles are composed of a fibre glass mat base. Ceramic coated mineral granules are tightly embedded in specially refined, water-resistant asphalt. XT25 Shingles have self-sealing adhesive. Shingles are laid over 12mm ply board.

### ***Applicable Standards***

ASTM D 3018, Type 1  
ASTM D 3462  
ASTM D 1922 Tear Strength  
ASTM E 108 Fire Resistance: Class A  
ASTM D 3161, Type 1 Wind Resistance

### ***Technical Data***

Weight - 11kg per m2 (approx) not including ply board (ply 9kg per m2)  
Dimension - Overall 30cm x 90cm  
Shingles per m2 - 9 Shingles  
Weather Exposure - 12.5 cm  
Rafter Centres- 600cc

*Any further inquiries should be directed to the office of A.S.I. on the above numbers*