

A.S.I.

AUSTRALASIAN SHINGLE IMPORTERS
SUPPLY & FIXERS OF IMPORTED ASPHALT SHINGLES

P O BOX 81 MORNINGTON 3931
A C N 087 873 327

22 CARBINE WAY MORNINGTON 3931
TEL: 03 5975 4944 MOB: 0412 070 146
FAX: 03 5975 2752

CERTAINTED SPECIFICATION INFORMATION **HIGHLAND SLATE Roofing Shingles**

Product Description

Highland Slate Roofing Shingles are designed for use on sloped roofs only. Only the Highland Slate shingle combines the highest wind resistance with classic beauty. Highland Slates oversized construction and unique design creates a wonderful slate like appearance.

Highland Slate Shingles are composed of a fibre glass mat base. Ceramic coated mineral granules are tightly embedded in specially refined, water-resistant asphalt. Highland Slate Shingles have dual self-sealing adhesive strips. Shingles are laid over 12mm ply board.

Applicable Standards

ASTM D 3018 Type 1
ASTM D 3462 Including tear strength and nail pull
ASTM E 108 Fire Resistance: Class A
ASTM D 3161 175km Wind Resistance
Lifetime Warranty against manufacturing defects

Technical Data

Weight - 12kg per m2 (approx) not including ply board (ply 9kg per m2)
Dimension - Overall 45cm x 90cm
Shingles per m2 - 6 Shingles
Weather Exposure - 20 cm
Rafter Centres- 600cc

Any further inquiries should be directed to the office of A.S.I. on the above numbers